



# AHB

## WATER PIPE HEATING CABLE, FIXED RESISTANCE, PRE-TERMINATED

Each AHB cable consists of a tough XLPE inner insulation, a continuous ground braid and weather resistant PVC outer jacket. AHB units are activated and de-activated by an integral energy-saving thermostat. Each cable is UL Listed to Canadian Safety Standards and CSA Certified when used in accordance with instructions on water-filled metal or plastic pipes.



CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
AHB013 *	3' length, 21 watts	10	6	0-13627-10950-6	
AHB016 *	6' length, 42 watts	10	7	0-13627-10951-3	
AHB019 *	9' length, 63 watts	10	9	0-13627-10952-0	
AHB112 *	12' length, 84 watts	10	10	0-13627-10953-7	
AHB115 *	15' length, 105 watts	10	11	0-13627-10954-4	
AHB118 *	18' length, 126 watts	5	7	0-13627-10955-1	
AHB124	24' length, 168 watts	5	8	0-13627-10956-8	
AHB130	30' length, 211 watts	5	9	0-13627-10957-5	
AHB140	40' length, 280 watts	5	12	0-13627-10958-2	
AHB160	60' length, 420 watts	5	15	0-13627-10959-9	
AHB180	80' length, 560 watts	5	20	0-13627-10960-5	
GTXAHB	STARTER KIT: 2 each of *'d above		19	0-13627-10948-3	
GWJAHB	JUMBO KIT: 5 each of *'d above		55	0-13627-10949-0	



# FREEZE FREE®

## SELF-REGULATING, CUT-TO-LENGTH CABLE

**Freeze Free®** – This self-regulating pipe heating cable automatically varies its heat output with changes in surrounding temperature. Freeze Free cable helps keep plastic and metal water pipes from freezing to -60°F/-51°C. A braided metal jacket provides an electrical ground as well as protection against damage in dry locations. Freeze Free cable is available on reels of 100 feet, 300 feet and 500 feet and can be cut to desired lengths per application. Pre-packaged lengths of 5 feet and 15 feet are also available. Cables are rated at 3 watts per foot, 120 Vac at 50°F/10°C; 75-foot maximum circuit length, 3-foot minimum circuit length. Freeze Free cable is UL Listed to US and Canadian Safety Standards and CSA Certified.



**10802 Fused Plug and End Seal** – This connection kit provides the specially designed fused plug to connect one Freeze Free heater into an electrical outlet and a cable end seal which helps ensure safe and proper usage of the Freeze Free cable.

CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS	
2102	100' reel Freeze Free	1	5	0-13627-06895-7		
2302	300' reel Freeze Free	1	13	0-13627-06896-4		
2502	500' reel Freeze Free	1	20	0-13627-06894-0		
10802	Connection Kit – clamshell pkg	10	3	0-13627-10802-8		
10803	Connection Kit – polybagged pkg	25	5	0-13627-10803-5		
FFEC	End Seals – 5/bag	10	2	0-13627-06946-6		
10805	5' pre-packaged Freeze Free Kit	5	4	0-13627-10805-9		
10815	15' pre-packaged Freeze Free Kit	5	6	0-13627-10815-8		
4102	100' display: (1) reel; (10) 10802	1	8	0-13627-06897-1		
4302	300' display: (1) reel; (20) 10802; (10) EH-38; (10) HCA	1	17	0-13627-06898-8		
NPRO50	50' Pro Pack: (1) reel; (3) 10803; (1) HCA	1	3	0-13627-10798-4		
NPRO100	100' Pro Pack: (1) reel; (6) 10803; (1) HCA	1	6	0-13627-10799-1		

# FREEZE FREE<sup>®</sup> ACCESSORIES

**EH38 Pre-set Thermostat** – The Pre-set Thermostat automatically energizes the heating cable at temperatures lower than 38°F/3°C, eliminates the need for unplugging heating cables each spring and reduces the risk of frozen pipes. EH38 can control other electrical devices that need to be activated when the temperature approaches the freezing point. It is rated at 15 amps, with resistive load at 125 Vac. The Pre-set Thermostat is UL Listed to US and Canadian Safety Standards.



**HCA Application Tape** – The HCA Application Tape is the best tape to use with Freeze Free<sup>®</sup> cable. It comes in thirty feet of clear tape, rated for temperature so as not to lose its adhesive properties, and is printed with the words ELECTRICALLY HEATED PIPE for easy identification. One per package. ½ inch x 10 yards.

**CS Caution Labels** – Reduces the possibility of accidents and liability with easy-to-read caution labels. Five per bag.

CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
EH38	Pre-set Thermostat	10	3	0-13627-09938-8	
HCA	Application Tape: ½" x 30'	10	2	0-13627-06945-9	
CS	Heated Pipe Caution Labels, 5 per bag	1	.25	0-13627-09924-1	

## PSR

### SELF-REGULATING, PRE-TERMINATED CABLE

PSR is a parallel resistance, self-regulating cable provided in pre-terminated lengths with factory sealed connections. The cable is manufactured with a water-resistant TPE outer jacket. Cables are rated at 5 watts per foot at 50°F/10°C. 120 Vac models have an integral three-wire plug with pilot light; 240 Vac models have a three-wire pigtail. PSR cables are UL Listed to Canadian Safety Standards and CSA Certified for ordinary locations.



CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS	
PSR1006	6' length, 30 watts, 120 Vac	5	10	0-13627-06907-7		
PSR1012	12' length, 60 watts, 120 Vac	5	14	0-13627-06908-4		
PSR1018	18' length, 90 watts, 120 Vac	5	14	0-13627-06913-8		
PSR1024	24' length, 120 watts, 120 Vac	5	14	0-13627-06909-1		
PSR1050	50' length, 250 watts, 120 Vac	5	23	0-13627-06910-7		
PSR1075	75' length, 375 watts, 120 Vac	2	13	0-13627-06911-4		
PSR1100	100' length, 500 watts, 120 Vac	2	16	0-13627-06912-1		
PSR2006	6' length, 30 watts, 240 Vac	5	10	0-13627-06867-4		
PSR2012	12' length, 60 watts, 240 Vac	5	14	0-13627-06868-1		
PSR2018	18' length, 90 watts, 240 Vac	5	14	0-13627-06873-5		
PSR2024	24' length, 120 watts, 240 Vac	5	14	0-13627-06869-8		
PSR2050	50' length, 250 watts, 240 Vac	5	23	0-13627-06870-4		
PSR2075	75' length, 375 watts, 240 Vac	2	13	0-13627-06871-1		
PSR2100	100' length, 500 watts, 240 Vac	2	16	0-13627-06872-8		